

Screwdriver

www.wellpneumatic.com



PC-5600 1/4" Composite Air Impact Screwdriver

- In the standard condition is more efficient than the same level tools
- The outer diameter is smaller which even female can use easily
- Special design for lower noise @70 dBA
- The F/R function can use by single hand



PC-5400 1/4" Reversible Air Impact Screwdriver

- Double rocking dog clutch
- Single hand reversible
- Side exhaust
- Bit Holder : 13mm



PC-0400 1/4" Reversible Air Impact Screwdriver

- Double rocking dog clutch
- Single hand reversible
- Side exhaust
- Bit Holder : 13mm



PC-0401 1/4" Clutch Adjustable Air Screwdriver

- Quick change bit retainer
- Pistol grip design
- Internal adjustable clutch
- Easy control trigger and fully reversible
- built-in muffler for noise reduction



PC-0600 1/4" Reversible Cushion Clutch Air Screwdriver

- Clutch type with high torque
- Composite lightweight housing reduces effects on operator's hands
- One hand operation for forward/ reverse control
- Non- section switch lever design , easy to press the lever for speed controlling
- Handle exhaust design to reduce the noise and dust rebound
- Adjust torque easily and prevent worker adjust random

Specification

Model No.	Screw Size Capacity	Free Speed	Retainer Capacity		Max. Torque		Avg. Air Cons.		Overall Length		Net Weight		Air Hose	Sound Pressure	Vibration Level	Air Inlet
	mm	rpm	inch	mm	ft-lbs	Nm	cfm	l/min	inch	mm	lb	kg	inch	dBA	m/s ²	inch
PC-5400	TBD	12000	1/4	6.4	33.9	46	TBD		8.5	215	1.5	0.7	1/4	80	TBD	1/4
PC-5600	4-5	10000	1/4	6.4	26	35	4.5	127.4	7	178	1.5	0.7	1/4	89	5.8	1/4
PC-0400	4-5	13000	1/4	6.4	26	35	7	198.2	5.6	143	2	0.8	1/4	88	12	1/4

Specification

Model No.	Screw Size Capacity	Free Speed	Retainer Capacity		Max. Torque		Avg. Air Cons.		Overall Length		Net Weight		Air Hose	Sound Pressure	Vibration Level	Air Inlet
	mm	rpm	inch	mm	ft-lbs	Nm	cfm	l/min	inch	mm	lb	kg	inch	dBA	m/s ²	inch
PC-0401	4	18000	1/4	6.4	9.6	13	7	200	8.5	215	2.7	1.2	3/8	83	4.2	1/4
PC-0600	6	2500	1/4	6.4	12.5	17	10	283	8.3	212	2.4	1.1	TBD	88	TBD	1/4