

PA-0013

Quick Change Chisel Retainer

- Universal design for 0.401" shank chisels
- New patent retainer, directly inserts chisel without pull back collar
- Press inside ring to disengage the retainer for removing chisels
- Securely holds the chisel in place to prevent chisel from coming out of the air hammer



For 0.401" shank chisels
and air hammers



Press inside ring
to remove chisels



Directly inserts chisel
without pull back collar



Steel ball and inner ring design
for securely holding the chisel



PP-0014

Needle Scaler Attachment

- Convert any air hammer with 0.401" round shank into a needle scaler
- New patent designed, only needs to screw attachment onto tool
- 3mm x 180mm x 19pcs needle attachment
- Changes needles quickly with a C-Ring to lock on the attachment
- Ideal for cleaning and removing paint, rust, dirt or weld slag



For 0.401" round
shank air hammers



Changes needles
with a C-Ring



Needles specification
3mm x 180mm x 19pcs



Screw attachment
onto tool easily



Accessory

PA-0011

Metal Shear Attachment

- Convert any power or electrical (18V-20V) drills and impact screwdriver (1/4" Hex) into a power metal shear
- Shear regulator to adjust the space between shear blades
- SUJ2 spring steel shear for long using time
- 20 gauge(0.8mm) cutting capacity
- 360° rotating head for optimum tool clearance and material flow

PP-0012

Nibbler Attachment

- Convert any power or electrical (18V-20V) drills and impact screwdriver (1/4" Hex) into a power nibbler
- Excellent cutting effect creates a precision, burr-free edge
- Adjustable cutting head for different direction
- Quick change design for replacing punch and die
- 18 gauge(1.55mm) cutting capacity
- 360° rotating head for either left or right-hand usage

Spring Steel Shear

for long using time

Shear Regulator

to adjust the space between shear blades

Rotating Head

to adjust the space between shear blades

Excellent Cutting Effect

creates a precision, burr-free edge

Cut in Any Direction

follow the profile of the material

Quick Change

design for replacing punch and die



PA-0017

Angle Attachment for Electric Drill

- High-speed industrial bearings allow this attachment to handle up to 120NM and 20,000RPM
- Only 58mm which allows it to fit in hard to reach angles
- Even for air drills because of durable 3 bearings designed
- Run-out <0.2mm for preventing the shank broken on the tool
- Durable metal die-cast housing, steel gear guarantees the strength extended life
- DIN 3126 & ISO 1173-C 6.3 high-grade steel 1/4" hex driver shank

360° adjustable head
suitable for different working application



Foldable side handle can be
locked into 0°, 45°, and 90°



Standard 1/4" hex driver



Suitable for power or cordless drills
with 9.5mm and 14mm bit holder



PA-1000

3in1 (17-19-21mm) Nut Socket for Electric Drill

- Work efficiently: Features 3 internal hex sizes: 17, 19, 21mm
- In one socket for a variety of applications
- Suitable for electric drill with 1/4" (6.35mm) hex driver
- Ideal for loosening and tightening nuts
- Design for double-headed bit of 65mm

Features 3 internal hex sizes
17, 19, 21mm in one socket



Design for double-headed bit of 65mm



Suitable for electric drill
with 1/4" hex driver



Screw attachment
onto tool easily



Accessory

PA-0015
PA-0016

Random Orbital Head Adapter

- Ideal for electric / air grinder transform palm sander function.
- Convenient non-vacuum pad applies to 10000 to 13000rpm electric/air grinder.
- Threaded Adapter Plate 12000rpm Max. 5mm orbital diameter.
- Low vibration provide smoother & quiet operation.
- Remove material rapidly and gives you a perfect finish.
- Tool spindle size for option : M14x2 / M10x1.5 / 5/8"-11UNC
- Tool pad for option : 5" (125mm) or 6" (150mm)

3 spindle & 2 pad
size for option



Install and remove easily



Change your grinder
into a sander tool



www.wellpneumatic.com

PA-3315 1/4" Regulator Swivel Connector

- Ergonomic 360° swivel hose connector reduces hand fatigue and less stress on the wrists while handling
- High operator flexibility and work productivity
- An air-floating lifting positioning patents, more convenient in use
- Equipped with speed regulator for the different working application
- Ideal for air tools such as grinders, sanders, glue guns, drills, and etc
- This 360° universal swivel with 1/4-Inch Male NPT X 1/4-Inch Female NPT



PA-3316 1/4" Swivel Connector

- Ergonomic 360° swivel hose connector reduces hand fatigue and less stress on the wrists while handling
- High operator flexibility and work productivity
- An air-floating lifting positioning patents, more convenient in use
- Ideal for air tools such as grinders, sanders, glue guns, drills, and etc
- This 360° universal swivel with 1/4-Inch Male NPT X 1/4-Inch Female NPT



PA-3317 1/4" Regulator four Rotational Connector

- Ergonomic 360° swivel hose connector reduces hand fatigue and less stress on the wrists while handling
- High operator flexibility and work productivity
- An air-floating lifting positioning patents, more convenient in use
- Equipped with speed regulator for the different working application
- Ideal for air tools such as grinders, sanders, glue guns, drills, and etc
- This 360° universal swivel with 1/4-Inch Male NPT X 1/4-Inch Female NPT



Specification

Model No.	Air Flow Range		Net Weight		Air Inlet	Flow Content	Material
	cfm	l/min	lb	g	inch		
PA-3315	26.5	751	0.1	60	1/4	Yes	Stainless Steel Aluminum
PA-3316	26.5	751	0.1	60	1/4	No	Stainless Steel Aluminum
PA-3317	26.5	751	0.1	60	1/4	Yes	Stainless Steel Aluminum



Color Typex

Air Plug & Quick Coupler

COLOR TYPEX Various color to separate air plug and coupler, including Aro, Truflate, Milton, Orion and Nitto type.

SWIVEL DESIGN Air plug and connector rotated minimizes hose twisting for improved control.

QUICK CHANGE Universal Air quick coupler design with swivel the ring to lock air plug inside for safety use.

DURABLE Steel ring insert can perform with greater durability for universal air quick coupler series.



Air Plug

- Air plug and connector rotated minimizes hose twisting for improved control
- Lightweight only 150g and durable 12L14 steel will not scratch or damage the work pieces
- Connecting air hose with 1/4"

Swivel Connector

Nitto

Milton

Aro

Truflate

Orion

Specification

Model No.	Type	Air Cons. (@30PSI)	Air Cons. (@120PSI)	Max. Pressure	Burst Pressure	Working Temp.	Air Inlet	Material
		cfm	cfm	kg/cm ²	PSI	°C	inch	
PA-3100	Swivel Connector	10.85	11.55	15	800	-25~50	1/4 (NPT/PT)	12L14 Steel
PA-3110	Nitto	10.85	11.55	15	800	-25~50	1/4 PT	12L14 Steel
PA-3120	Milton	10.85	11.55	15	800	-25~50	1/4 NPT	12L14 Steel
PA-3130	Aro	10.85	11.55	15	800	-25~50	1/4 NPT	12L14 Steel
PA-3140	Truflate	10.85	11.55	15	800	-25~50	1/4 NPT	12L14 Steel
PA-3150	Orion	10.85	11.55	15	800	-25~50	1/4 PT	12L14 Steel

Quick Air Coupler

- One-touch design for user operated easy, inserted direct the air tools with the air plug
- The composite material reinforced with steel ring insert can perform with greater durability
- Lightweight only 85g and durable Nylon + PA 12L14 steel will not scratch or damage
- Connecting air hose with 1/4", 3/8" or 1/2" male and female thread



Specification

Type	Air Core (@90PSI)	Air Core (@120PSI)	Max Pressure	Burst Pressure	Working Temp.	Air Inlet	Material
	cm	cm	kg/cm²	PSI	°C	inch	
Nitto	11.2	12.3	15	800	-25~50	Male or Female Type with 1/4, 3/8, 1/2 PT	Nylon + PA with 12L14 Steel
Milton	11.2	12.3	15	800	-25~50	Male or Female Type with 1/4, 3/8, 1/2 NPT	Nylon + PA with 12L14 Steel
Aro	11.2	12.3	15	800	-25~50	Male or Female Type with 1/4, 3/8, 1/2 NPT	Nylon + PA with 12L14 Steel
Truflate	11.2	12.3	15	800	-25~50	Male or Female Type with 1/4, 3/8, 1/2 NPT	Nylon + PA with 12L14 Steel
Orion	11.2	12.3	15	800	-25~50	Male or Female Type with 1/4, 3/8, 1/2 PT	Nylon + PA with 12L14 Steel

3 in 1 Quick Air Coupler

- USA Type for Milton / Aro / True-Flate
- European Type for Milton / Aro / Orion
- Universal coupler fit with three most popular interchange connectors
- Swivel the ring to lock air plug inside for safety use
- One-touch design for user operated easy, inserted direct the air tools with the air plug
- The composite material reinforced with steel ring insert can perform with greater durability
- Lightweight only 85g and durable Nylon + PA 12L14 steel will not scratch or damage
- Connecting air hose with 1/4", 3/8" or 1/2" male and female thread



Specification

Type	Air Core (@90PSI)	Air Core (@120PSI)	Max Pressure	Burst Pressure	Working Temp.	Air Inlet	Material
	cm	cm	kg/cm²	PSI	°C	inch	
USA	11.2	12.3	15	800	-25~50	Male or Female Type with 1/4, 3/8, 1/2 NPT	12L14 Steel
EUROPEAN	11.2	12.3	15	800	-25~50	Male or Female Type with 1/4, 3/8, 1/2 PT	12L14 Steel